






FLIR i60

FLIR i60 is a lightweight, professional infrared camera with a high quality visual digital camera of 2.3 Mpxels. The FLIR i60 offers scalable fusion, Picture in Picture for professional analysis. New FLIR MeterLink technology, wireless Bluetooth connection with Extech Instruments, Copy to USB and Bluetooth voice annotation functionality will make the FLIR i60 your favorite tool. The Li Ion battery allows work for 5 hours without interruption of loading. The unique FLIR LED lights makes it possible to work effectively even in dark environments. FLIR QuickReport™ software makes it possible to analyze IR and visual pictures captured in field back in the office.

-  IR resolution 180 x 180 pixels
-  Digital camera 1536 x 1536 pixels
-  Lightweight 600 g
-  MeterLink™
-  Copy to USB

-  Laser marker in IR image
-  Fusion (scalable Picture in Picture)
-  5 hours battery
-  LED lights
-  21 languages



FLIR i60 Features

- **Digital Camera** — 2.3 Megapixels with built-in LED lights provides sharp images regardless of lighting conditions
- **Picture in Picture (PiP)** — Displays resizable IR image super-imposed over a digital image
- **Wide Temperature Range** — Measures from -20 °C to +350 °C targeting electrical and industrial applications
- **MeterLink™** — Wirelessly transmit data from clamp or moisture meter to your infrared camera
- **± 2% Accuracy** — Reliable temperature measurement
- **IR Window Auto-Correction** — Automatic sensitivity adjustment when inspecting high voltage through safety IR windows
- **Annotations** — Record voice comments via Bluetooth wireless headset
- **Laser Pointer with marker in IR image** — Accurate positioning with marker in the IR image
- **Micro SD Card** — Stores more than 2000 radiometric JPEG images
- **Copy to USB** — Upload images and measurement findings to USB stick



180 x 180 pixel resolution



Fusion (Scalable PiP)



Copy to USB



MeterLink™



What is MeterLink™?

MeterLink displays and documents readings from your Extech moisture- or clamp meter directly on your infrared image using Bluetooth wireless connection.*

MeterLink, a FLIR industry-first technology, will greatly improve your diagnostics, save time annotating readings, eliminate data errors, and add more customer value to your reports.

*Only on selected Extech models

FLIR i60 Specifications


Imaging and optical data	
Field of view (FOV) /	25° × 25° / 0.10 m (0.33 ft.)
Minimum focus distance	
Spatial resolution (IFOV)	2.42 mrad
Thermal sensitivity/NETD	<0.10 °C (<0.18 °F) @ +25 °C (+77 °F) / 100 mK
Image frequency	9 Hz
Focus	Manual
Focal Plane Array (FPA) /	Uncooled microbolometer / 7.5–13 µm
Spectral range	
IR resolution	180 × 180 pixels
Image presentation	
Display	Built-in 3.5 in. LCD, 256k colors, 240 × 320 pixels
Image modes	IR image, visual image, Picture in Picture, thumbnail gallery
Picture in Picture	Scalable IR area on visual image
Measurement	
Object temperature range	–20 to +120 °C (–4 to +248 °F) 0 to +350 °C (+32 to +662 °F)
Accuracy	±2 °C (±3.6 °F) or ±2% of reading
Measurement analysis	
Spotmeter	Center spot
Area	1 box/full image with min./max.
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Emissivity correction	Variable from 0.1 to 1.0 or selected from list of materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
IR window Auto-Correction	Automatic, based on inputs of optics/window transmission and temperature
Set-up	
Menu commands	Palettes (Black and White, Iron and Rainbow), image adjustment (auto/manual)
Set-up commands	Local adaptation of units, language, date and time formats; automatic shutdown, display intensity
Storage of images	
Image storage	Standard JPEG, including measurement data, on memory card
Image annotations	
Voice	60 seconds
External sensors	Possible to connect (Bluetooth®): Extech Moisture Meter MO297 Extech Clamp Meter EX845
Video streaming	
Radiometric IR-video streaming	Full dynamic to PC using USB (approximately 1 Hz)

Digital camera	
Built-in digital camera	2.3 Mpixels (1536 × 1536 pixels), and two LED lights
Digital camera, focus	Minimum focus distance 0.4 m (1.3 ft.)
Laser pointer	
Laser	Semiconductor AlGaInP diode laser, Class 2
Laser alignment	Position is automatic displayed on the IR image
Data communication interfaces	
Interfaces	USB-A: Connect external USB device (copy to memory stick) USB Mini-B: Data transfer to and from PC / streaming MPEG-4
Power system	
Battery	Li Ion (field replaceable), 5 hours operating time
Charging system	In camera, AC adapter, 2-bay charger or 12 V from a vehicle
Power management	Automatic shutdown (user selectable)
AC operation	AC adapter, 90–260 VAC, 50/60 Hz, 12 V output to camera
Environmental data	
Operating temperature range	–15 to +50 °C (+5 to +122 °F)
Storage temperature range	–40 to +70 °C (–40 to +158 °F)
Humidity (operating and storage)	IEC 68-2-30/24 h 95% relative humidity +25 °C to +40 °C (+77 °F to +104 °F)
Encapsulation	IP 54 (IEC 60529)
Bump	25 g (IEC 60068-2-29)
Vibration	2 g (IEC 60068-2-6)
Physical data	
Camera weight, incl. battery	0.60 kg (1.32 lb)
Camera size (L × W × H)	235 × 90 × 175 mm (9.3 × 3.5 × 6.9 in.)
Scope of delivery	
Packaging, contents: Hard transport case, Infrared camera with lens, Battery, Bluetooth headset, Bluetooth USB dongle, Bluetooth USB micro adapter, Calibration certificate, FLIR QuickReport™ PC software CD-ROM, Memory card with adapter, Power supply, Printed Getting Started Guide, USB cable, User documentation CD-ROM, Warranty extension card or Registration card	
Optional software	
QuickPlot/ ResearchIR	A software for entry to mid-level R&D applications for visualizes thermal patterns
FLIR Reporter Standard/ Professional	A powerful yet easy-to-use tool to generate comprehensive and professional infrared inspection reports.

Applications



Motor: Bearing Problem



Motor: Internal Winding Problem



Building: Heat Loss



Specifications and prices subject to change without notice.

Copyright © 2010 FLIR Systems. All right reserved including the right of reproduction in whole or in part in any form.

FLIR Systems Co Ltd.
Headquarters Asia Pacific
Room 1613 – 15, Tower 2,
Grand Central Plaza,
138 Shatin Rural Committee Road,
N.T, Hong Kong
Tel: +852 2792 8955
Fax: +852 2792 8952
Email: flir@flir.com.hk

FLIR Systems (Shanghai) Co., Ltd
Head Office China
Tel: +86 21 5169 7628
Email: info@flir.cn

FLIR Systems Japan KK
Tel: +81 3 6277 5681
Email: info@flir.jp

FLIR Systems Australia Pty Ltd
Head office Australia
Tel: +61 3 9550 2800
Email: info@flir.com.au

FLIR Systems Korea Co., Ltd
Tel: +82 2 541 1834
Email: flir@flirkorea.com

FLIR Systems Taiwan
Representative Office
Tel: +886 2 2757 9662
Email: flir@flir.com.hk

FLIR Systems India Pvt Limited
C/o Swedish Trade Council
Tel: +91-11-46067100
Email: flir@flir.com.hk



www.flir.com/thg